

SCHEDA TECNICA - TECHNICAL FEATURES - FICHE TECHNIQUE

CARATTERISSTICHE FEATURES CARACTERISTIQUES		UNITÀ DI MISURA UNIT OF MEASURE UNITE DE MESURE	VALORI RESULT RESULTAT	METODO DI PROVA TESTING METHOD METHODE	
PESO / WEIGHT / POIDS		g/sm / mq gr / sqm	≥ 360		
COMPOSIZIONE / CONTENTS / COMPOSITION		%	100% POLYESTER F.R.		
CARICO DI ROTTURA	ORDITO/WARP/CHAINE	DaN	≥ 50	BSI 2576/86	
	TRAMA/WEFT/TRAME		≥ 75		
ALLUNGAMENTO A ROTTURA ALONGATION AT BREAK PERCENTAGE ALLONGEMENT A LA RUPTURE	ORDITO/WARP/CHAINE	%	≥ 20	BSI 2576/86	
	TRAMA/WEFT/TRAME		≥ 35		
RESISTENZA ALLA LACERAZIONE RESISTANCE TO TEARING RESISTANCE A LA DECHIRURE	ORDITO/WARP/CHAINE	DaN	≥ 35	UNI EN ISO 13937-3	
	TRAMA/WEFT/TRAME		≥ 35		
RESISTENZA ALLO SCORRIMENTO FILE ALLA CUCITURA SEAM SLIPPAGE RESISTANCE A LA COUTURE	ORDITO/WARP/CHAINE	mm.	≤ 1,5	BSI 2543/95 BSI 3320/88	
	TRAMA/WEFT/TRAME		≤ 2		
RAPPORTO DISEGNO	ORDITO/WARP/TRAME	cm.			
	TRAMA/WEFT/TRAME				
RESISTENZA ALL'ABRASIONE ABRASION RESISTANCE RESISTANCE A L'ABRASION		Cicli Cycles	>= 75.000	BSI 2543/95 BSI 5690/91	
RESISTENZA AL PILLING RESISTANCE TO PILLING RESISTANCE AU PILLING		Grado Grade	4	UNI EN ISO 12945-2/02	
SOLIDITÀ DEL COLORE COLOUR FASTNESS SOLIDITE COULEUR	ALLA LUCE LIGHT LUMIERE	Scala blu blue wool references Echelle des blues	≥ 5		
	LAMPADA ALLO XENO XENON LAMP LAMPE A ARC AU XENON	Scala blu blue wool references Echelle des blues	≥ 5		
SOLIDITÀ DEL COLORE COLOUR FASTNESS SOLIDITE COULEUR	SFREGAMENTI RUBING FROTTEMENT	SECCO / DRY / A SEC	Scala grigi Grey scale Echelle des gris	≥ 5	BSI 1006 X12/90
		UMIDO / WET / UMIDE		≥ 4/5	
	SFREGAMENTI SOLVENTI ORGANICI RUBING ORGANIC SOLVENT SOLVENTS ORGANIQUES	CAMBIO DI COLORE CHANGE IN COLOUR CHANGE DE COULEUR	Scala grigi Grey scale Echelle des gris	≥ 4	BSI 1006 D02/90
		SCARICO STAINING DECARGE	Scala grigi Grey scale Echelle des gris	≥ 4	
MANUTENZIONE CLEANING ENTRETIEN					

CARATTERISTICHE ANTIFIAMMA / *FLAMMABILITY* / CARACTERISTIQUES NON FEU
CLASSE 1
M1 (NFP92-512 1986)
BS - 5852 (part 1, source 0,1)
B1 (DIN 4102)
TB 117 (2000) CALIFORNIA TEST





VIGANO

FURNISHING FABRICS & VELVETS

VIGANÒ S.p.A. - Via Volta, 2 - 23895 Nibionno Lc - Italy - Tel. 031.69231 - Fax 031.690318 - www.vigano.it - vigano@vigano.it
MADE IN ITALY

VIGANO



VIGANO

FURNISHING FABRICS & VELVETS

BILBAO FLAME RETARDANT

BILBAO

FR

CLASSE 1

B1

M1

IMO

BS-5852 (part 1, source 0,1)